

LTL Machine Sizes & Electrical Requirements

W L H = Width Length Height

' = feet

" = inches

	W	L	H	Elect.	Amp.	Elect.	Air CFM	Pressure
Band Saw	1'	2'	2'	110/60	2	1 Phase	---	---
Belt Sander	1'	2'	2'	110/60	2	1 Phase	---	---
Blind Cut-down Machine -Retail	90"	40"	25"	110/60	20	1 Phase	---	---
	26"	40"	16"	220/60	20	1 Phase	---	---
Blind Cut-down Machine -Steel	6'	4'	4'	110/60	15	1 Phase	1	100
Bottom Rail Drill Air	1 1/2'	1 1/2'	2'	---	---	---	13	80
Bottom Rail Drill Elect.	1 1/2'	1 1/2'	2'	110/60	4	1 Phase	---	---
Bottom Rail Drill Elect. Hold Down	1 1/2'	1 1/2'	2'	110/60	4	1 Phase	---	---
Cart Horizontal	3'	4'	4'	---	---	---	---	---
Cart Vertical	2'	4'	4 1/2'	---	---	---	---	---
Combo Table	3'	8'	3'	---	---	---	---	---
Cord Cutter	1'	1'	1'	110/60	2	1 Phase	---	---
Csaw	2'	2'	2'	110/60	15	1 Phase	1	80
De-Ionizer for FAW / FAD	---	---	---	110/60	0.2	1 Phase	12	80
De-Ionizer Hand Held	---	---	---	110/60	0.2	1 Phase	8	80
Dust Collector	1 1/2'	2 1/2'	4 1/2'	110/60	15	1 Phase	---	---
FAST (Fully Automatic Saw Table) uses Mobil DTE oil ISO 150 6Y782	4'	22 1/2'	7'	220/60	20	3 Phase	1	80
	---	---	---	110/60	15	1 Phase	---	---
FAW, FAD	3'	17'	5'	110/60	3	1 Phase	3	80
Grommet Machine	1'	2'	2'	110/60	3	1 Phase	---	---
Head Rail Dies	2 1/2'	2'	2'	---	---	---	3	100
Head Rail Machine	3'	22 1/2'	5'	---	---	---	3	100
Head Rail Machine w/ computer	3'	22 1/2'	5'	110/60	3	1 Phase	3	100
Head Rail Machine with HR	3'	28 1/2'	5'	---	---	---	3	100
Lift Rack	4'	8'	9' to 14'	110/60	9	---	---	---
Shutter Saw	4'	22 1/2'	7'	220/60	20	3 Phase	1	80
	---	---	---	110/60	15	1 Phase	---	---
Sliding Miter Saw	3'	10'	5 1/2'	110/60	15	1 Phase	1	80
SSS Stackable Steel Shelving	41"	108"	42"	---	---	---	1	80
Step2	6"	9"	12"	---	---	---	1	80
STEP3, CW22, CW24	2'	8 1/2'	5'	---	---	---	2	80
UpCut Saw USG	3'	12 1/2'	7'	230/60	60	3 Phase	1	70
				460/60	25	3 Phase	1	70